
SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Product Name: Chain Lubricant Aerosol

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Lubricant

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: GardX International Limited
- Address of Supplier: Lake House
2 Port Way,
Port Solent
PO6 4TY
Portsmouth
UK
- Telephone: +44 (0)1243 376426
- Email: product@gardxgroup.com
- Name of Importer: GardX New Zealand Limited
- Address of Importer: 739 Chapel Road
Howick
Auckland
New Zealand
- Telephone: 0800 242 739
- Email: info@gardx.co.nz

1.4 Emergency telephone number

- Emergency Telephone: PCN 131 126. CNN: 1012486. For 24/7 multilingual advice for spill, leak, fire, exposure or accident, call chemtrek @ +65 3163 8374 or +61 2 9037 2994

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classified as a hazardous substance in accordance with the criteria of Hazardous Substances (Safety Data Sheets) Notice 2017

GHS Classification

Flammable Aerosol Category 1 H222
Pressurised Gas H229

HSNO Classification - Aerosol Category 1

2.2 Label elements

SECTION 2: Hazards identification (....)

- Signal Word: Danger

Hazard statements

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

Precautionary statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

P102 - Keep out of reach of children.

P501 - Dispose of contents/container to an authorised waste collection point

2.3 Other hazards

- None

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics

Concentration: 20-50%

CAS Number: Not available

EC Number: 920-107-4

Categories: Asp. Tox. 1

H Statements: H304

Petroleum gases, liquified <0.1% 1,3-butadiene

Concentration: 20-50%

CAS Number: 68476-85-7

Categories: Flam. Gas 1, Press. Gas

H Statements: H220, H280

Non-Hazardous Components

Concentration: Balance

CAS Number: Proprietary

Categories: Not applicable

H Statements: Not applicable

SECTION 4: First aid measures

4.1 Description of first aid measures

Ingestion

Rinse mouth with water (only if the person is conscious)
If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

Contact with eyes

If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes
Remove contact lenses, if present and easy to do. Continue rinsing.
Seek medical attention if ill effects occur

Contact with skin

Remove contaminated clothing
Wash affected area with plenty of soap and water
When in doubt or symptoms persist, seek medical attention

Inhalation

Remove person to fresh air and keep comfortable for breathing.
Seek medical attention if ill effects occur

4.2 Most important symptoms and effects, both acute and delayed

Ingestion

Aspiration hazard
Causes damage to the lungs through repeated or prolonged exposure if inhaled

Contact with eyes

May cause irritation

Contact with skin

Repeated exposure may cause skin dryness or cracking.

Inhalation

In cases of severe exposure, dizziness, confusion, headache or stupor may develop

4.3 Indication of any immediate medical attention and special treatment needed

- Treat symptomatically

SECTION 5: Firefighting measures

5.1 Extinguishing media

- In case of fire use water spray or fog, alcohol resistant foam, dry chemical or carbon dioxide
- Do not use water jets

5.2 Special hazards arising from the substance or mixture

- Extremely Flammable
- Explosion risk.
- Pressurised container: May burst if heated.

5.3 Advice for firefighters

SECTION 5: Firefighting measures (....)

- Wear Positive-Pressure Breathing Apparatus
 - Keep container(s) exposed to fire cool, by spraying with water
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Wear protective clothing as per section 8
- Do not smoke
- Avoid breathing dust/fume/gas/mist/vapours/spray.
- Shut off all ignition sources

6.2 Environmental precautions

- Do not allow to enter public sewers and watercourses
- If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3 Methods and material for containment and cleaning up

- Ensure adequate ventilation
- Shut off all ignition sources
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Contain leaking liquid in earth or sand and remove to safe place when solid
- Seek expert advice for removal and disposal of all contaminated materials and wastes

6.4 Reference to other sections

- None
-

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Avoid breathing dust/fume/gas/mist/vapours/spray.
- Ensure adequate ventilation
- Do not spray on naked flame or any incandescent material

7.2 Conditions for safe storage, including any incompatibilities

- Extremely Flammable
- Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C
- Store in a well-ventilated place. Keep cool.

7.3 Specific end use(s)

- Not available
-

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics

Exposure limit (in house): 150 ppm 1200 mg/m³ (8 hour TWA)

Petroleum gases, liquified <0.1% 1,3-butadiene

SECTION 8: Exposure controls/personal protection (....)

Exposure limit (in house): 1000 ppm 1750 mg/m³ (8 hour TWA)
WEL (short term): 15 minutes - 1250 ppm

8.2 Exposure controls

- Wear suitable protective clothing, including eye/face protection and gloves (nitrile are recommended)
- Engineering controls should be provided which maintain airborne concentrations below the relevant guidelines
- Ensure adequate ventilation
- Eyewash bottles should be available
- Do not eat, drink or smoke when using this product.

8.3 Environmental exposure controls

- Do not allow to enter public sewers and watercourses
- If contamination of drainage systems or water courses is unavoidable, immediately inform appropriate authorities

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Physical state: liquid
- Colour: amber
- Odour: Characteristic odour
- Melting point/Range: not available
- Freezing point/Range: not available
- Boiling Point/Range: Boiling point: -40 °C to 270 °C
- Flammability: Extremely Flammable
- Lower explosive limit: 1.8% (in air)
- Upper explosive limit: 9.5% (in air)
- Flashpoint: -41°C (CC)
- Autoignition Temperature: not available
- Decomposition temperature: not available
- pH: not applicable
- Kinematic viscosity: not available mm²/s
- Solubility in water: Insoluble in water
- Partition Coefficient (n-Octanol/Water): not available
- Vapour pressure: not available
- Density: Approx. 0.725 g/cm³
- Relative vapour density: not available
- Particle characteristics: not available

9.2 Other information

- No information available

SECTION 10: Stability and reactivity**10.1 Reactivity**

SECTION 10: Stability and reactivity (....)

- No hazardous reactions known if used for its intended purpose

10.2 Chemical stability

- This article is considered stable under normal conditions

10.3 Possibility of hazardous reactions

- No hazardous reactions known if used for its intended purpose

10.4 Conditions to avoid

- Keep away from heat and sources of ignition

10.5 Incompatible materials

- Incompatible with oxidizing substances

10.6 Hazardous decomposition products

- Decomposition products may include nitrogen and carbon oxides
-

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD₅₀ (oral, rat): >5000 mg/kg

LD50 (dermal rabbit) : >5000 mg/kg

LC₅₀ (inhalation, rat): >5000 mg/l/4h

Petroleum gases, liquified <0.1% 1,3-butadiene

Not available

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking

Serious eye damage/irritation

May cause redness and irritation

Respiratory or skin sensitisation

Based on the available data, the classification criteria are not met

Germ cell mutagenicity

No evidence of mutagenic effects

Carcinogenicity

No evidence of carcinogenic effects

Reproductive toxicity

No evidence of reproductive effects

STOT (specific target organ toxicity) - single exposure

Based on the available data, the classification criteria are not met

STOT (specific target organ toxicity) - repeated exposure

Based on the available data, the classification criteria are not met

SECTION 11: Toxicological information (....)

Aspiration hazard

Aspiration hazard

Causes damage to the lungs through repeated or prolonged exposure if inhaled

11.2 Information on other hazards

- Not available

SECTION 12: Ecological information**12.1 Toxicity**

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC₅₀ (fish): 1000 mg/l (96 hr)

EC₅₀ (Daphnia magna): 1000 mg/l (48 hr)

IC₅₀ (algae): 1000 mg/l (72 hr)

Petroleum gases, liquified <0.1% 1,3-butadiene

No information available

12.2 Persistence and degradability

- Biodegradable

12.3 Bioaccumulative potential

- No information available

12.4 Mobility in soil

- No information available

12.5 Results of PBT and vPvB assessment

- Not a PBT according to REACH Annex XIII

12.6 Endocrine disrupting properties

- Not applicable

12.7 Other adverse effects

- Water Hazard Class: 1 (Company)

SECTION 13: Disposal considerations

Do not discharge into drains or the environment, dispose to an authorised waste collection point

Disposal should be in accordance with local, state or national legislation

Dispose of product in packaging in a way that is consistent with the Hazardous Substances (Disposal) Notice 2017 and the Act.

SECTION 14: Transport information**14.1 UN number or ID number**

SECTION 14: Transport information (....)

- UN No.: 1950
 - 14.2 UN proper shipping name
 - Proper Shipping Name: Aerosols, flammable
 - 14.3 Transport hazard class(es)
 - Transport according to NZS 5433 (Transport of Hazardous Substances on Land)
 - ADR Hazard Class: 2.1
 - ADR Classification Code: 5F
 - ADR-RID Labels: 2.1
 - IMDG Hazard Class: 2.1
 - ICAO Hazard Class: 2.1
 - 14.4 Packing group
 - ADR Packing Group: Not applicable
 - IMDG Packing Group.: Not applicable
 - ICAO Packing Group: Not applicable
 - 14.5 Environmental hazards
 - Presents little or no hazard to the environment
 - 14.6 Special precautions for user
 - IMDG EmS: F-D, S-U
 - Tunnel Code: (D)
 - 14.7 Maritime transport in bulk according to IMO instruments
 - Not applicable
-

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - National regulations - New Zealand
 - Classified as a hazardous substance in accordance with the criteria of Hazardous Substances (Hazard Classification) Notice 2020 (and amended)

Chemical Name	HSNO Chemical Classification
Petroleum gases, liquefied - 68476-85-7	Aerosol Category 1

 - EPA New Zealand HSNO approval code or group standard - HSR002515
 - See section 8 for national exposure control parameters
 - This product is not subject to the following international agreements:
 - Montreal Protocol (Ozone depleting substances)
 - The Stockholm Convention (Persistent Organic Pollutants)
 - The Rotterdam Convention (Prior . . Informed Consent)
 - 15.2 Chemical safety assessment
 - Not available
-

SECTION 16: Other information

SECTION 16: Other information (....)

Text not given with phrase codes where they are used elsewhere in this safety data sheet:- H220: Extremely flammable gas. H280: Contains gas under pressure; may explode if heated. H304: May be fatal if swallowed and enters airways.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: Exposure controls/personal protection

TWA - Time-weighted average DNEL - Derived no-effect level WEL - Workplace exposure limit

LD - Lethal dose LC - Lethal concentration IC - Inhibitory concentration EC - Effective concentration

DISCLAIMER - Please read carefully as this limits your ability to claim damages.

DISCLAIMER - Please read carefully as this limits your ability to claim damages.

Your use of this product is beyond the control of Marott Graphic Services (UK) Ltd (and our associated companies) ("the Company") and is subject to our standard terms and conditions of sale. The Company shall have no liability to the fullest extent permitted by law for any claims, losses, demands, damages or expenses arising out of or in any way connected with, the possession, use and application of handling, storage, or disposal of this product including but not limited to direct, indirect, incidental or consequential loss or damages, compensatory damages, loss of profit or anticipated savings, whether based on breach or contract or warranty, delict, or tort, product liability or otherwise. Your use of this product will be deemed as your acceptance of this disclaimer. This does not limit in any way our liability by law for death or personal injury caused from our negligence.

--- end of safety datasheet ---
