SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
 - Product Name: GARDXCP Chain Lubricant Aerosol
 - UFI: KP00-D06P-A00D-CX28
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - Lubricant
- 1.3 Details of the supplier of the safety data sheet
 - Name of Supplier: Automotosol s.r.o.
 - Address of Supplier: Rybna 716/24, Praha 1, 110 00, Czech Republic
 - Telephone: +420 222 703288Email: info@automotosol.cz
- 1.4 Emergency telephone number
 - Emergency Telephone: For 24/7 multilingual advice for spill, leak, fire, exposure, or accident

call Chemtrec @ 1-800-424-9300 or +442038850382. CNN:

1012486

Republic of Ireland (NPIC): 01 809 2166 (8am-10pm)

Northern Ireland: 999 or contact GP

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
 - Regulation (EC) No 1272/2008
 - CLP: Flam. Aerosol 1, Press. Gas, Compressed gas H222, H229
- 2.2 Label elements



- Signal Word: Danger

Hazard statements

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

Precautionary statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

Datasheet Number: GARDXCP Chain Lubricant Aerosol - v1.0.0 Prometheus v1.6.7.8

SECTION 2: Hazards identification (....)

P410+P412 - Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F. P102 - Keep out of reach of children.

Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking

2.3 Other hazards

- None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics

Concentration: 20-50% CAS Number: Not available EC Number: 920-107-4

REACH Registration Number: 01-2119453414-43-xxxx

Categories: Asp. Tox. 1 H Statements: H304, EUH066

Acute toxicity estimate: >5000 mg/kg (oral), >5000 mg/kg (dermal), >5000 mg/l/4h

(inhalation)

Petroleum gases, liquified <0.1% 1,3-butadiene

Concentration: 20-50% CAS Number: 68476-85-7 EC Number: 270-704-2

REACH Registration Number: This product is either exempt from REACH or does not

meet the minimum volume threshold for a chemical safety

assessment (CSA)

Categories: Flam. Gas 1, Press. Gas

H Statements: H220, H280

Acute toxicity estimate: Not available

SECTION 4: First aid measures

4.1 Description of first aid measures

Ingestion

Rinse mouth with water (only if the person is conscious)

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

Contact with eyes

If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes

Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical attention if ill effects occur

Contact with skin

Datasheet Number: GARDXCP Chain Lubricant Aerosol - v1.0.0

SECTION 4: First aid measures (....)

Remove contaminated clothing

Wash affected area with plenty of soap and water

When in doubt or symptoms persist, seek medical attention

Inhalation

Remove person to fresh air and keep comfortable for breathing. Seek medical attention if ill effects occur

4.2 Most important symptoms and effects, both acute and delayed

Ingestion

Aspiration hazard

Causes damage to the lungs through repeated or prolonged exposure if inhaled

Contact with eyes

May cause irritation

Contact with skin

Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis

Repeated exposure may cause skin dryness or cracking.

Inhalation

In cases of severe exposure, dizziness, confusion, headache or stupor may develop

- 4.3 Indication of any immediate medical attention and special treatment needed
 - Treat symptomatically

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
 - In case of fire use water spray or fog, alcohol resistant foam, dry chemical or carbon dioxide
 - Do not use water jets
- 5.2 Special hazards arising from the substance or mixture
 - Extremely Flammable
 - Explosion risk.
 - Pressurised container: May burst if heated.
- 5.3 Advice for firefighters
 - Wear Positive-Pressure Breathing Apparatus
 - Keep container(s) exposed to fire cool, by spraying with water

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 - Wear protective clothing as per section 8
 - Do not smoke
 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 - Shut off all ignition sources
- 6.2 Environmental precautions
 - Do not allow to enter public sewers and watercourses

Datasheet Number: GARDXCP Chain Lubricant Aerosol - v1.0.0 Prometheus v1.6.7.8

SECTION 6: Accidental release measures (....)

- If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities
- 6.3 Methods and material for containment and cleaning up
 - Ensure adequate ventilation
 - Shut off all ignition sources
 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - Contain leaking liquid in earth or sand and remove to safe place when solid
 - Seek expert advice for removal and disposal of all contaminated materials and wastes
- 6.4 Reference to other sections
 - None

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 - Ensure adequate ventilation
 - Do not spray on naked flame or any incandescent material
- 7.2 Conditions for safe storage, including any incompatibilities
 - Extremely Flammable
 - Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C
 - Store in a well-ventilated place. Keep cool.
- 7.3 Specific end use(s)
 - Not available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics Exposure limit (in house): 150 ppm 1200 mg/m³ (8 hour TWA)

Petroleum gases, liquified <0.1% 1,3-butadiene

Exposure limit (in house): 1000 ppm 1750 mg/m³ (8 hour TWA)

WEL (short term): 15 minutes - 1250 ppm

8.2 Exposure controls





- Wear suitable protective clothing, including eye/face protection and gloves (nitrile are recommended)
- Engineering controls should be provided which maintain airborne concentrations below the relevant guidelines
- Ensure adequate ventilation

SECTION 8: Exposure controls/personal protection (....)

- Eyewash bottles should be available
- Do not eat, drink or smoke when using this product.
- 8.3 Environmental exposure controls
 - Do not allow to enter public sewers and watercourses
 - If contamination of drainage systems or water courses is unavoidable, immediately inform appropriate authorities

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
 - Physical state: liquid
 - Colour: amber
 - Odour: Characteristic odour
 - Melting point/Range: not available
 - Freezing point/Range: not available
 - Boiling Point/Range: Boiling point: -40 °C to 270 °C
 - Flammability: Extremely Flammable
 - Lower explosive limit: 1.8% (in air)
 - Upper explosive limit: 9.5% (in air)
 - Flashpoint: -41°C (CC)
 - Autoignition Temperature: not available
 - Decomposition temperature: not available
 - pH: not applicable
 - Kinematic viscosity: not available mm²/s
 - Solubility in water: Insoluble in water
 - Partition Coefficient (n-Octanol/Water): not available
 - Vapour pressure: not available
 - Density: Approx. 0.725 g/cm³
 - Relative vapour density: not available
 - Particle characteristics: not available
- 9.2 Other information
 - No information available

SECTION 10: Stability and reactivity

- 10.1 Reactivity
 - No hazardous reactions known if used for its intended purpose
- 10.2 Chemical stability
 - This article is considered stable under normal conditions
- 10.3 Possibility of hazardous reactions
 - No hazardous reactions known if used for its intended purpose
- 10.4 Conditions to avoid
 - Keep away from heat and sources of ignition
- 10.5 Incompatible materials
 - Incompatible with oxidizing substances

Datasheet Number: GARDXCP Chain Lubricant Aerosol - v1.0.0 Prometheus v1.6.7.8

SECTION 10: Stability and reactivity (....)

10.6 Hazardous decomposition products

- Decomposition products may include nitrogen and carbon oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD₅₀ (oral, rat): >5000 mg/kg

LD50 (dermal rabbit) : >5000 mg/kg LC₅₀ (inhalation, rat): >5000 mg/l/4h

Petroleum gases, liquified <0.1% 1,3-butadiene

2050 (IIIIIalation, 1at). > 3000 mg//411

Not available

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking

Serious eye damage/irritation

May cause redness and irritation

Respiratory or skin sensitisation

Based on the available data, the classification criteria are not met

Germ cell mutagenicity

No evidence of mutagenic effects

Carcinogenicity

No evidence of carcinogenic effects

Reproductive toxicity

No evidence of reproductive effects

STOT (specific target organ toxicity) - single exposure

Based on the available data, the classification criteria are not met

STOT (specific target organ toxicity) - repeated exposure

Based on the available data, the classification criteria are not met

Aspiration hazard

Aspiration hazard

Causes damage to the lungs through repeated or prolonged exposure if inhaled

11.2 Information on other hazards

- Not available

SECTION 12: Ecological information

12.1 Toxicity

Datasheet Number: GARDXCP Chain Lubricant Aerosol - v1.0.0

SECTION 12: Ecological information (....)

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC₅₀ (fish): 1000 mg/l (96 hr)

EC₅₀ (Daphnia magna): 1000 mg/l (48 hr)

IC₅₀ (algae): 1000 mg/l (72 hr)

Petroleum gases, liquified <0.1% 1,3-butadiene

No information available

- 12.2 Persistence and degradability
 - Biodegradable
- 12.3 Bioaccumulative potential
 - No information available
- 12.4 Mobility in soil
 - No information available
- 12.5 Results of PBT and vPvB assessment
 - Not a PBT according to REACH Annex XIII
- 12.6 Endocrine disrupting properties
 - Not applicable
- 12.7 Other adverse effects
 - Water Hazard Class: 1 (Company)

SECTION 13: Disposal considerations

Do not discharge into drains or the environment, dispose to an authorised waste collection point

Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information



- 14.1 UN number or ID number
 - UN No.: 1950
- 14.2 UN proper shipping name
 - Proper Shipping Name: Aerosols, flammable
- 14.3 Transport hazard class(es)
 - ADR Hazard Class: 2.1
 - ADR Classification Code: 5F
 - ADR-RID Labels: 2.1IMDG Hazard Class: 2.1
 - ICAO Hazard Class: 2.1
- 14.4 Packing group

Datasheet Number: GARDXCP Chain Lubricant Aerosol - v1.0.0

Prometheus v1.6.7.8

SECTION 14: Transport information (....)

ADR Packing Group: Not applicableIMDG Packing Group: Not applicableICAO Packing Group: Not applicable

14.5 Environmental hazards

- Presents little or no hazard to the environment

14.6 Special precautions for user

IMDG EmS: F-D, S-UTunnel Code: (D)

14.7 Maritime transport in bulk according to IMO instruments

- Not applicable

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - This Safety Data Sheet is provided in compliance with the EC Regulations 1907/2006, 1272/2008, 2015/830 and 2020/878

15.2 Chemical safety assessment

- Not available

SECTION 16: Other information

Text not given with phrase codes where they are used elsewhere in this safety data sheet:-EUH066: Repeated exposure may cause skin dryness or cracking. H220: Extremely flammable gas. H280: Contains gas under pressure; may explode if heated. H304: May be fatal if swallowed and enters airways.

DISCLAIMER - Please read carefully as this limits your ability to claim damages.

Your use of this product is beyond the control of Marott Graphic Services (UK) Ltd (and our associated companies) ("the Company") and is subject to our standard terms and conditions of sale. The Company shall have no liability to the fullest extent permitted by law for any claims, losses, demands, damages or expenses arising out of or in any way connected with, the possession, use and application of handling, storage, or disposal of this product including but not limited to direct, indirect, incidental or consequential loss or damages, compensatory damages, loss of profit or anticipated savings, whether based on breach or contract or warranty, delict, or tort, product liability or otherwise. Your use of this product will be deemed as your acceptance of this disclaimer. This does not limit in any way our liability by law for death or personal injury caused from our negligence.

--- end of safety datasheet ---

Datasheet Number: GARDXCP Chain Lubricant Aerosol - v1.0.0

Prometheus v1.6.7.8