

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 1: IDENTIFICATION**1.1 Product identifier:** Ceramic Paint Protection**Other means of identification:**

Not relevant

1.2 Recommended uses and any restrictions on use or supply:

Relevant uses (Professional users): Vehicle Underseal; water repeller

Relevant uses (Industrial user): Vehicle Underseal; water repeller

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Supplier's details:GARDX INTERNATIONAL LTD
LAKE HOUSE, 2 PORT WAY, PORT SOLENT,
PO6 4TY PORTSMOUTH - UNITED KINGDOM
Phone: +44 (0)1243 376426
product@gardx.co.uk
www.gardx.co.ukGardX New Zealand Limited
739 Chapel Road,
Howick,
Auckland,
New Zealand 2145

0800 242 739

1.4 Emergency phone number: PC No. 0800 764 766. CCN: 1012486. For 24/7 multilingual advice for spill, leak, fire, exposure or accident, call Chemtrec @ +65 3163 8374 or + 64 9 801 0034**SECTION 2: HAZARD IDENTIFICATION****2.1 Classification of the substance or mixture:****Hazardous Substances (Hazard Classification) Notice 2020.:**

This product was classified in accordance with Hazardous Substances (Hazard Classification) Notice 2020.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Asp. Tox. 1: Aspiration hazard, Category 1, H304

Eye Dam. 1: Serious eye damage, Category 1, H318

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Corr. 1B: Skin corrosion, Category 1B, H314

Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements, including precautionary statements:**Hazardous Substances (Hazard Classification) Notice 2020.:**

Danger

**Hazard statements:**

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 2: HAZARD IDENTIFICATION (continued)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/face protection.
P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor/physician.
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

Substances that contribute to the classification

Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics (30 - <60 %); Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanam (CAS: 475645-84-2) (<10 %); 3-aminopropyltriethoxysilane (CAS: 919-30-2) (<10 %)

2.3 Other hazards which do not result in classification:

Not relevant

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Not available

3.2 Mixtures:

Chemical description: Mixture of polymers, dispersants and organic compounds

Components:

In accordance with Part B: Concentration cut-offs for ingredients in mixtures for purpose of section 3 of Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: Not available	Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336 - Danger	30 - <60 %
CAS: Not available	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics Asp. Tox. 1: H304 - Danger	10 - <30 %
CAS: 475645-84-2	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanam Acute Tox. 4: H302; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Flam. Liq. 2: H225; Skin Corr. 1B: H314; Water-react. 3: H261 - Danger	<10 %
CAS: 919-30-2	3-aminopropyltriethoxysilane Acute Tox. 4: H302; Flam. Liq. 4: H227; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	<10 %
CAS: 56275-01-5	Silanol-trimethylsilyl modified Q Resin Flam. Liq. 4: H227	<10 %
CAS: 302776-68-7	Hexyl 2-(1-(diethylaminohydroxyphenyl)methanoyl)benzoate Aquatic Chronic 4: H413	<10 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 First aid instructions according to each relevant route of exposure;:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

Remove the affected person from the area of exposure, provide them with fresh air, and keep them at rest. In severe cases such as cardiorespiratory arrest, administer artificial respiration techniques if properly trained (CPR, oxygen provision, etc.) and seek immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 4: FIRST-AID MEASURES (continued)**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of medical attention and its urgency:

Not relevant

SECTION 5: FIRE-FIGHTING MEASURES**5.1 Information on the appropriate type of extinguishers or fire-fighting agents:****Appropriate type of extinguishers or fire-fighting agents:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Inappropriate type of extinguishers or fire-fighting agents:

Water jet

5.2 Advice on specific hazards that may arise from the substance:

Contains substances that react with water producing extremely flammable gases.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions from accidental spills and release;:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Advice on how to contain and clean up a spill or release:

DO NOT USE WATER TO CLEAN.

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 4 °C

Maximum Temp.: 40 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Occupational exposure limits:**

Substances whose workplace exposure standards (WES) have to be monitored in the work environment:

There are no applicable occupational exposure limits for the substances contained in the product

8.2 Engineering controls:

A.- Identification of the specific types of personal protective equipment

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: AP)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.1 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.
 Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.1 mm, Conditions of use: Splashing)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.
	Work clothing	Replace before any evidence of deterioration.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Transparent
Colour:	Colourless
Odour:	Ammoniacal
Odour threshold:	Not relevant *

Volatility:

Initial boiling point and boiling range:	176 °C
Vapour pressure at 20 °C:	158 Pa
Vapour pressure at 50 °C:	1239.73 Pa (1.24 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	Not relevant *
Relative density at 20 °C:	0.792 - 0.812
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	<20.5 mm ² /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Insoluble in water
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	28 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	300 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *

Particle characteristics:

Median equivalent diameter:	Not relevant *
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 10: STABILITY AND REACTIVITY

10.1 Chemical reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 List of conditions to avoid or prevent a hazardous situation:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Precaution

10.5 Information on incompatible substances or materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Precaution	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Information on hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

May be fatal if swallowed and enters airways.

Other information:

Not relevant

Product-specific toxicological information:

Acute toxicity		Genus
LD50 oral	>2000 mg/kg	

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Hydrocarbons, C9-C10, n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Not relevant	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Not relevant	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation mist	>5.26 mg/L (4 h)	Rat
Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanam CAS: 475645-84-2	LD50 oral	>301 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation gases	>20000 mg/L	
	LC50 inhalation vapour	>20 mg/L	
	LC50 inhalation dust	>5 mg/L	
3-aminopropyltriethoxysilane CAS: 919-30-2	LD50 oral	1491 mg/kg	Rat
	LD50 dermal	4000 mg/kg	Rabbit
	LC50 inhalation vapour	>20 mg/L	
Silanol-trimethylsilyl modified Q Resin CAS: 56275-01-5	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation dust	>5 mg/L	
Hexyl 2-(1-(diethylaminohydroxyphenyl)methanoyl)benzoate CAS: 302776-68-7	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation dust	>5 mg/L	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	3581.73 mg/kg (Calculation method)	0 %
Dermal	200000 mg/kg (Calculation method)	0 %
LC50 inhalation vapour	>20 mg/L (4 h) (Calculation method)	0 %

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Ecotoxicity (aquatic and terrestrial):

Acute toxicity:

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Not relevant	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae
Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanam CAS: 475645-84-2	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae
3-aminopropyltriethoxysilane CAS: 919-30-2	LC50	934 mg/L (96 h)	Danio rerio	Fish
	EC50	331 mg/L (48 h)	N/A	Crustacean
	EC50	603 mg/L (72 h)	Desmodesmus subspicatus	Algae
Hexyl 2-(1-(diethylaminohydroxyphenyl)methanoyl)benzoate CAS: 302776-68-7	LC50	>100 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	>100 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	>100 mg/L (72 h)	Desmodesmus subspicatus	Algae

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
3-aminopropyltriethoxysilane CAS: 919-30-2	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	67 %

12.3 Potential to be bioaccumulative:

Not relevant

12.4 Mobility in soil:

Not relevant

Insoluble in water

12.5 Results of PBT and vPvB assessment:

Not relevant

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Appropriate and achievable disposal methods:

Special precautions to be taken during disposal:

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See epigraph 6.2.

Regulations related to waste management:

Legislation related to waste management:

Consolidated Imports and Exports (Restrictions) Prohibition Order (No 2) 2004
Consolidated Hazardous Substances (Disposal) Notice 2017

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to NZS 5433.1:2012 Transport of dangerous goods on land

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN2920
- 14.2 UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanam; Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics)
- 14.3 UN dangerous goods class and subsidiary risk:** 8
- Labels:** 8, 3
- 14.4 UN Packing Group:** II
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number:** UN2920
- 14.2 UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanam; Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics)
- 14.3 UN dangerous goods class and subsidiary risk:** 8
- Labels:** 8, 3
- 14.4 UN Packing Group:** II
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
- Special regulations: 274
- EmS Codes: F-E, S-C
- Physico-Chemical properties: see section 9
- Limited quantities: 1 L
- Segregation group: Not relevant
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



- 14.1 UN number:** UN2920
- 14.2 UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanam; Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics)
- 14.3 UN dangerous goods class and subsidiary risk:** 8
- Labels:** 8, 3
- 14.4 UN Packing Group:** II
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not relevant

CONTINUED ON NEXT PAGE

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023 Revised: 13/05/2025 Version: 3 (Replaced 2)

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations specific for the product in question:**

- New Zealand Inventory of Chemicals (NZIoC): *Cyclosiloxanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen siloxanes, reaction products with 3-(triethoxysilyl)-1-propanol (475645-84-2); 3-aminopropyltriethoxysilane (919-30-2); Poly(dimethylsiloxane), viscosity 350 cP (25°C) (63148-62-9); Silanol-trimethylsilyl modified Q Resin (56275-01-5); Hexyl 2-(1-(diethylamino)hydroxyphenyl)methanoyl benzoate (302776-68-7)*

- Substances listed in the Montreal Protocol: Not relevant

- Substances listed in the Rotterdam Convention: Not relevant

- Substances listed in the Stockholm Convention: Not relevant

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Relevant regulatory requirements:

Health and Safety at Work (Hazardous Substances) Regulations 2017

Health and Safety at Work Act 2015

Consolidated Hazardous Substances (Labelling) Notice 2017

Consolidated Hazardous Substances (Packaging) Notice 2017

Consolidated Hazardous Substances (Hazardous Property Controls) Notice 2017

Consolidated Hazardous Substances (Importers and Manufacturers) Notice 2015

SECTION 16: OTHER INFORMATION**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with Schedule: Content and format of safety data sheets (clause 7) of Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

H304: May be fatal if swallowed and enters airways.

H226: Flammable liquid and vapour.

H314: Causes severe skin burns and eye damage.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

Hazardous Substances (Hazard Classification) Notice 2020.:

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Dam. 1: H318 - Causes serious eye damage.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Flam. Liq. 4: H227 - Combustible liquid.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Water-react. 3: H261 - In contact with water releases flammable gases.

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<https://www.epa.govt.nz/>

Abbreviations and acronyms:

CONTINUED ON NEXT PAGE



Safety data sheet

According to Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

**Ceramic Paint Protection
L1354**

Date of compilation: 25/07/2023

Revised: 13/05/2025

Version: 3 (Replaced 2)

SECTION 16: OTHER INFORMATION (continued)

HSNO Act: Hazardous substances and new organisms Act
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
CL50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

END OF SAFETY DATA SHEET

Date of compilation: 25/07/2023

Revised: 13/05/2025

Version: 3 (Replaced 2)